

Implementation file: tcl3dCgQuery.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dCg
Filename: tcl3dCgQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the Cg module.

Name: tcl3dCgGetVersion - Get Cg version string.

Synopsis: tcl3dCgGetVersion {}

Description: Return the version string of the wrapped Cg library. The version is returned as "Major.Minor.Patch".

See also: tcl3dOglGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dCgUtil.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dCg
 Filename: tcl3dCgUtil.tcl

Author: Paul Obermeier

Description: Tcl module with miscellaneous utility procedures related to the Cg module.

Name: tcl3dCgGetError - Check for a Cg error.

Synopsis: tcl3dCgGetError { contextId { msg "" } }

Description: contextId : Cg context identifier
 msg : Additional message string

Check, if a Cg related error has occurred. The Cg context - as returned by cgCreateContext - has to be supplied with parameter "contextId".

The procedure returns an empty string, if no error has occurred. Otherwise it returns the additional message string, the error number and Cg error message as supplied by the Cg library as a formatted string.

See also: tcl3dOglGetError

Name: tcl3dCgGetProfileList - Get a list of Cg profile names.

Synopsis: tcl3dCgGetProfileList { }

Description: Return a Tcl list of Cg profile names.

The list consists of (key,value) pairs, where key is the profile name, like CG_PROFILE_FP30 and value is either 1, if the corresponding profile is supported, or 0, if it is not available.

See also: tcl3dCgFindProfile
 tcl3dCgFindProfileByNum

Name: tcl3dCgFindProfile - Find a supported Cg profile.

Synopsis: tcl3dCgFindProfile { args }

Description: args : Profile names

Find the first profile supported by the Cg implementation from the profile names supplied in "args". If successful, it returns the profile name, otherwise an empty string.

See also: tcl3dCgGetProfileList
 tcl3dCgFindProfileByNum

Name: tcl3dCgFindProfileByNum - Find a supported Cg profile.

Synopsis: tcl3dCgFindProfileByNum { profileNum }

Description: profileNum : int (CGprofile)

Find a profile name by it's numerical value supplied in "profileNum".
If successful, it returns the profile name, otherwise an empty string.

Note: The procedure does not check, if the profile is supported. Use tcl3dCgFindProfile to check for support by the underlying Cg implementation.

See also: tcl3dCgGetProfileList
 tcl3dCgFindProfile

Name: tcl3dCgPrintProgramInfo - Print Cg program info.

Synopsis: tcl3dCgPrintProgramInfo { progId { progFile "Unknown" } }

Description: progId : Cg Program identifier
 progFile : string

Print the profile name and the name of the entry function of the Cg program identified by "progId".
The Cg program identifier is the identifier as returned by calls to the cgCreateProgram family.
An optional parameter "progFile" can be supplied to specify the name of the file containing the Cg program source code.

See also:

Implementation file: tcl3dDemoHeightMap.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
Filename: tcl3dDemoHeightMap.tcl

Author: Paul Obermeier

Description: Tcl module to create a heightmap from a photo image. This functionality is needed for NeHe tutorial 45.

Name: tcl3dDemoUtilHeightmapFromPhoto - Create a heightmap from an image.

Synopsis: tcl3dDemoUtilHeightmapFromPhoto {
 phImg flHeightScale flResolution }

Description: phImg : string (Photo image identifier)
 flHeightScale : float
 flResolution : float

Create two Tcl3D vectors containing the vertices and texture coordinates of a heightmap created from the image data of photo image "phImg".
The height values can be scaled with "flHeightScale".
"flResolution" indicates how many pixels form a vertex.

The two vectors and the number of vertices generated are returned as a Tcl list:
Index 0: Vertex vector
Index 1: Texture coordinates vector
Index 2: Number of vertices

See also:

Implementation file: tcl3dFTGLQuery.tcl

Copyright: 2007-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dFTGL
Filename: tcl3dFTGLQuery.tcl

Author: Paul Obermeier

Description: Tcl module with with query procedures related to the FTGL module.

Name: tcl3dFTGLGetVersion - Get FTGL version string.

Synopsis: tcl3dFTGLGetVersion {}

Description: Return the version string of the wrapped FTGL library. The version is returned as "Major.Minor.Patch". If FTGL is not wrapped or supported, an empty string is returned.

Note: FTGL does not support version numbers in the code, so the version number is hand-coded here.

See also: tcl3dOglGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dFTGLUtil.tcl

Copyright: 2006-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dFTGL
Filename: tcl3dFTGLUtil.tcl

Author: Paul Obermeier

Description: Tcl module with miscellaneous utility procedures related to the FTGL module.

Name: tcl3dFTGLGetBBox - Get bounding box of a string.

Synopsis: tcl3dFTGLGetBBox { font str }

Description: font : string (Font identifier)
str : string

Return the bounding box of string "str" displayed in font "font".
The bounding box is returned as a list of 6 values:
{ xmin ymin zmin xmax ymax zmax }
"font" must be an identifier as returned by one of the FTGL*Font functions (ex. FTGLBitmapFont).

See also:

Implementation file: tcl3dGl2psQuery.tcl

Copyright: 2007-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dGl2ps
Filename: tcl3dGl2psQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the GL2PS module.

Name: tcl3dGl2psGetVersion - Get GL2PS version string.

Synopsis: tcl3dGl2psGetVersion {}

Description: Return the version string of the wrapped GL2PS library. The version is returned as "Major.Minor.Patch".

See also: tcl3dOglGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dGl2psUtil.tcl

Copyright: 2006-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dGl2ps
Filename: tcl3dGl2psUtil.tcl

Author: Paul Obermeier

Description: Tcl module with miscellaneous utility procedures related to the GL2PS module.

Name: tcl3dGl2psCreatePdf - Create PDF from OpenGL content.

Synopsis: tcl3dGl2psCreatePdf { toglwin filename
 { title "Tcl3D Screenshot" }
 { drawBackground 0 }
 { producer "Tcl3D" } }

Description: toglwin : string (Togl identifier)
 filename : string
 title : string
 drawBackground : boolean
 producer : string

Create a PDF file from current Togl window content. The PDF is created from the Togl window identified by "toglwin" and written to file "filename". The following optional parameters set PDF specific values:
"title" is the name of the document title as listed in the document properties of the PDF file. If "drawBackground" is set to true, the background color of the Togl window is also used as the background color of the PDF document. Otherwise the PDF background color is set to white.
"procuder" is the name of the producer property as listed in the document properties of the PDF file.

See also:

Implementation file: tcl3dGuiAutoscroll.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)
2003 Kevin B Kenny <kennykb@users.sourceforge.net>

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
Filename: tcl3dGuiAutoscroll.tcl

Author: Paul Obermeier

Description: Tcl module to create scroll bars that automatically appear when a window is too small to display its content.

Name: tcl3dAutoscroll::autoscroll - Create auto scrollbar

Synopsis: tcl3dAutoscroll::autoscroll { w }

Description: w : string (Widget name)

Create a scroll bar that disappears when it is not needed, and reappears when it is.
The scroll bar "w" should already exist.

Side effects:
The widget command is renamed, so that the 'set' command can be intercepted and determine whether the widget should appear.
In addition, the 'Autoscroll' bind tag is added to the widget, so that the <Destroy> event can be intercepted.

See also: tcl3dAutoscroll::unautoscroll

Name: tcl3dAutoscroll::unautoscroll - Remove scrollbar from package control.

Synopsis: tcl3dAutoscroll::unautoscroll { w }

Description: w : string (Widget name)

Return a scrollbar to its normal static behavior by removing it from the control of this package.

"w" is the path name of the scroll bar, which must have previously had tcl3dAutoscroll::autoscroll called on it.

Side effects:
The widget command is renamed to its original name.
The widget is mapped if it was not currently displayed.
The widgets bindtags are returned to their original state.
Internal memory is cleaned up.

See also: tcl3dAutoscroll::autoscroll

Name: tcl3dAutoscroll::widgetCommand - Apply a widget command.

Synopsis: tcl3dAutoscroll::widgetCommand { w command args }

Description: w : string (Widget name)
command : string
args : argument list

Apply widget command "command" on 'autoscroll' scrollbar "w". Arguments to the commands can be supplied in "args".

Return whatever the widget command returns.

Side effects:

Has whatever side effects the widget command has. In addition, the 'set' widget command is handled specially, by gridding/packing the scroll bar according to whether it is required.

See also:

Name: `tcl3dAutoscroll::destroyed` - Destroy callback.

Synopsis: `tcl3dAutoscroll::destroyed { w }`

Description: `w` : string (Widget name)

Callback executed when automatic scroll bar "w" is destroyed.

Side effects:

Cleans up internal memory.

See also: `tcl3dAutoscroll::map`

Name: `tcl3dAutoscroll::map` - Mapping callback.

Synopsis: `tcl3dAutoscroll::map { w }`

Description: `w` : string (Widget name)

Callback executed when automatic scroll bar "w" is mapped.

Side effects:

Geometry of scroll bar's top-level window is constrained.

This procedure keeps the top-level window associated with an automatic scroll bar from being resized automatically after the scroll bar is mapped. This effect avoids a potential endless loop in the case where the resize of the top-level window resizes the widget being scrolled, causing the scroll bar no longer to be needed.

See also: `tcl3dAutoscroll::destroyed`

Name: `tcl3dAutoscroll::wrap` - Autoscroll all new scrollbars.

Synopsis: `tcl3dAutoscroll::wrap {}`

Description: Arrange for all new scrollbars to be automatically autoscrolled.

Side effects:

`::scrollbar` is overloaded to automatically autoscroll any new scrollbars.

See also: `tcl3dAutoscroll::unwrap`

Name: `tcl3dAutoscroll::unwrap` - Turn off automatic autoscrolling of new scrollbars.

Synopsis: `tcl3dAutoscroll::unwrap {}`

Description: Turn off automatic autoscrolling of new scrollbars. Does not effect existing scrollbars.

Side effects:

`::scrollbar` is returned to its original state

See also: `tcl3dAutoscroll::wrap`

Implementation file: tcl3dGuiConsole.tcl

Copyright: 2006-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
Filename: tcl3dGuiConsole.tcl

Author: Paul Obermeier

Description: Tcl module implementing a simple Tk console. It is used in the tcl3dsh, the Tcl3D Starpack. The implementation of this console window was taken from D. Richard Hipp's mktclapp.

Name: tcl3dConsoleCreate - Create a console window.

Synopsis: tcl3dConsoleCreate { w prompt title }

Description: w : string (Widget name)
prompt : string
title : string

Create a new console window "w". The window's title will be set to "title". The prompt inside the console's text widget will be set to "prompt".

Example:
tcl3dConsoleCreate .myConsole "tcl3d> " "Tcl3D Console"

See also:

Implementation file: tcl3dGuiToolhelp.tcl

```

Copyright:      2005-2010 Paul Obermeier (obermeier@tcl3d.org)

                See the file "Tcl3D_License.txt" for information on
                usage and redistribution of this file, and for a
                DISCLAIMER OF ALL WARRANTIES.

Module:         Tcl3D -> tcl3dOgl
Filename:       tcl3dGuiToolhelp.tcl

Author:        Paul Obermeier

Description:    Tcl module implementing a simple tool help widget.

Name:          tcl3dToolhelpInit - Initialize toolhelp module.

Synopsis:      tcl3dToolhelpInit { w { bgColor yellow }
                { fgColor black } }

Description:    w          : string (Widget name)
                bgColor   : string
                fgColor   : string

                Initialize the toolhelp module.
                The initialization function only needs to be called
                when non-standard background and foreground colors
                are needed.

See also:      tcl3dToolhelpAddBinding

Name:          tcl3dToolhelpShow - Display toolhelp message.

Synopsis:      tcl3dToolhelpShow { x y str }

Description:    x      : int
                y      : int
                str    : string

                Display the toolhelp window at widget relative
                coordinates (x, y) with message string "str".

                A typical usage is like follows:
                bind $w <Enter> "tcl3dToolhelpShow %X %Y [list $str]"

See also:      tcl3dToolhelpHide
                tcl3dToolhelpAddBinding

Name:          tcl3dToolhelpHide - Hide toolhelp message.

Synopsis:      tcl3dToolhelpHide {}

Description:    Hide the toolhelp message window.

See also:      tcl3dToolhelpShow
                tcl3dToolhelpAddBinding

Name:          tcl3dToolhelpAddBinding - Add binding for a toolhelp
                message.

Synopsis:      tcl3dToolhelpAddBinding { w str }

Description:    w      : string (Widget name)
                str    : string

                Add bindings to widget "w" to display message string
                "str" in a toolhelp window near the widget. The

```

toolhelp window is shown, when the mouse enters the widget and unmapped, when the mouse leaves the widget.

See also: `tcl3dToolhelpInit`

Implementation file: tcl3dGuiWidgets.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
Filename: tcl3dGuiWidgets.tcl

Author: Paul Obermeier

Description: Tcl module implementing some simple Tk widgets like scrolled listboxes and text widgets, as well as some widget and window handling utilities.

Name: tcl3dHaveAqua - Check, if windowing system is Aqua.

Synopsis: tcl3dHaveAqua {}

Description: Return true, if the windowing system is Apple's Aqua. Otherwise return false.

See also: tcl3dShowIndicator

Name: tcl3dShowIndicator - Check, if button indicators should be shown.

Synopsis: tcl3dShowIndicator {}

Description: Return true, if we want to show the indicators for radio- and checkbuttons. Currently we do this on a Mac running Aqua, because it looks very buggy otherwise.

See also: tcl3dHaveAqua

Name: tcl3dAddEvents - Add virtual events.

Synopsis: tcl3dAddEvents {}

Description: Add the following virtual events for cross-platform mouse event handling:
<<LeftMousePress>>
<<MiddleMousePress>>
<<RightMousePress>>

See also:

Name: tcl3dWinIsTop - Check, if widget is a top level window.

Synopsis: tcl3dWinIsTop { wid }

Description: wid : string
Return true, if widget "wid" is a top level window.

See also: tcl3dWinRaise

Name: tcl3dWinRaise - Raise a widget.

Synopsis: tcl3dWinRaise { wid }

Description: wid : string
Raise widget "wid" to the top of the widget layout

hierarchy.

See also: `tcl3dWinIsTop`

Name: `tcl3dSetFullScreenMode` - Put a widget into fullscreen mode.

Synopsis: `tcl3dSetFullScreenMode { wid }`

Description: `wid` : string

Put widget "wid" into fullscreen mode:
It's size is adjusted to fit the entire screen, window decoration is removed and the widget can not be resized.

See also: `tcl3SetWindowMode`

Name: `tcl3dSetWindowMode` - Put a widget into windowing mode.

Synopsis: `tcl3dSetWindowMode { wid w h }`

Description: `wid` : string
`w` : int
`h` : int

Put widget "wid" into windowing mode:
It's size is adjusted to width "w" and height "h", window decoration is enabled and the widget can be resized.

See also: `tcl3dSetFullScreenMode`

Name: `tcl3dSetScrolledTitle` - Set the title of a scrolled widget.

Synopsis: `tcl3dSetScrolledTitle { wid titleStr
 { fgColor "black" } }`

Description: `wid` : string
`titleStr` : string
`fgColor` : string

Set the title of scrolled widget "wid" to string "titleStr". The text color can be optionally specified with "fgColor". "fgColor" must be a valid Tk color name. "wid" must be a widget name returned from `tcl3dCreateScrolledWidget` or descendants.

See also: `tcl3dCreateScrolledWidget`

Name: `tcl3dCreateScrolledWidget` - Create a scrolled widget.

Synopsis: `tcl3dCreateScrolledWidget { wType wid titleStr args }`

Description: `wType` : string
`wid` : string
`titleStr` : string
`args` : list

Create a compound widget with horizontal and vertical scrollbars. The type of the widget is given with "wType" and must be a valid Tk widget like canvas or text. "wid" is the parent frame of the compound widget and must already exist. The compound widget may have a title string, which is given with "titleStr". If "titleStr" is an empty string, no title label will be generated.

With optional parameter "args" additional widget specific parameters may be supplied.
Return the identifier to the created master widget.

There exist several utility procedures for often used Tk widget types. See list below.

See also: `tcl3dSetScrolledTitle`
`tcl3dCreateScrolledFrame`
`tcl3dCreateScrolledListbox`
`tcl3dCreateScrolledText`
`tcl3dCreateScrolledCanvas`
`tcl3dCreateScrolledTable`
`tcl3dCreateScrolledTablelist`

Name: `tcl3dCreateScrolledFrame` - Create a scrolled frame widget.

Synopsis: `tcl3dCreateScrolledFrame { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled frame widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created frame widget.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Name: `tcl3dCreateScrolledListbox` - Create a scrolled listbox widget.

Synopsis: `tcl3dCreateScrolledListbox { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled listbox widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created listbox widget.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Name: `tcl3dCreateScrolledText` - Create a scrolled text widget.

Synopsis: `tcl3dCreateScrolledText { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled text widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created text widget.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Name: `tcl3dCreateScrolledCanvas` - Create a scrolled canvas widget.

Synopsis: `tcl3dCreateScrolledCanvas { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled canvas widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created canvas widget.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Name: `tcl3dCreateScrolledTable` - Create a scrolled tktable widget.

Synopsis: `tcl3dCreateScrolledTable { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled TkTable widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created TkTable widget.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Name: `tcl3dCreateScrolledTablelist` - Create a scrolled tablelist widget.

Synopsis: `tcl3dCreateScrolledTablelist { wid titleStr args }`

Description: `wid` : string
`titleStr` : string
`args` : list

Create a scrolled tablelist widget. "wid" specifies the parent frame of the created scrolled widget. "titleStr" specifies the string displayed as widget title. With optional parameter "args" additional widget specific parameters may be supplied. Return the identifier to the created tablelist widget.

Note: A "package require tablelist" must be issued before using this function.

See also: `tcl3dCreateScrolledWidget`
`tcl3dSetScrolledTitle`

Implementation file: tcl3dOdeQuery.tcl

Copyright: 2007-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOde
Filename: tcl3dOdeQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the ODE module.

Name: tcl3dOdeGetVersion - Get ODE version string.

Synopsis: tcl3dOdeGetVersion {}

Description: Return the version string of the wrapped ODE library. The version is returned as "Major.Minor.Patch".

Note: ODE does not support version numbers in the code, so the version number is hand-coded here.

See also: tcl3dOglGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dOglHelp.tcl

Copyright: 2009-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dOglHelp.tcl

Author: Paul Obermeier

Description: Tcl module with help and information procedures related to the OpenGL module.

Name: tcl3dOglGetFuncList - Get list of OpenGL and GLU functions.

Synopsis: tcl3dOglGetFuncList { what }
 what : string (Default "gl")
 Allowed values for what ar: "gl", "glu" or "all"

Description: Return a list of all wrapped OpenGL and/or GLU function names.

See also: tcl3dOglGetVersionList
 tcl3dOglIsFuncWrapped
 tcl3dOglGetVersionFuncs
 tcl3dOglGetVersionEnums

Name: tcl3dOglGetVersionList - Get list of OpenGL versions and extensions.

Synopsis: tcl3dOglGetVersionList {}

Description: Return a list of all wrapped OpenGL versions and extension names.
 The names are strings identical to their corresponding C defines.
 Examples:
 GL versions : GL_VERSION_1_5, GL_VERSION_3_2
 GL extensions: GL_ARB_vertex_program, GL_EXT_texture3D

See also: tcl3dOglGetFuncList
 tcl3dOglGetFuncVersion
 tcl3dOglGetVersionFuncs
 tcl3dOglGetVersionEnums

Name: tcl3dOglGetExtensionList - Get list of OpenGL extensions.

Synopsis: tcl3dOglGetExtensionList { {what "all"} }

Description: Return a list of OpenGL extension names.
 The names are strings identical to their corresponding C defines.
 Examples:GL_ARB_vertex_program, GL_EXT_texture3D

If "what" is equal to "all", all OpenGL extension names are returned.
 If "what" is equal to "glew", only the OpenGL extension names wrapped by GLEW are returned.
 If "what" is equal to "driver", only the OpenGL extension names supported by the driver and hardware of the actual machine are returned.

See also: tcl3dOglGetFuncList

```
tcl3dOglGetFuncVersion
tcl3dOglGetVersionList
tcl3dOglGetVersionFuncs
tcl3dOglGetVersionEnums
```

Name: tcl3dOglIsFuncWrapped - Check if OpenGL or GLU function is wrapped.

Synopsis: tcl3dOglIsFuncWrapped { func }

Description: Return true, if OpenGL or GLU function "func" is wrapped in Tcl3D. Otherwise return false.

Note: To check, if a function is supported by the used OpenGL driver, use procedure "tcl3dOglHaveFunc".

See also: tcl3dOglGetFuncList
tcl3dOglGetFuncSignature
tcl3dOglGetFuncVersion
tcl3dOglGetFuncDeprecated
tcl3dOglGetUrl

Name: tcl3dOglGetFuncSignature - Get the signature of an OpenGL or GLU function.

Synopsis: tcl3dOglGetFuncSignature { func {what "c"} }

Description: Return the signature of OpenGL or GLU function "func" as a string.
If "func" is not contained in the list of wrapped OpenGL functions (see tcl3dOglGetFuncList), an empty string is returned.

If "what" is equal to "c", the signature string is returned in C style notation. This is the default case.
If "what" is equal to "tcl", the signature string is returned in Tcl style notation.

Note: This procedure replaces the obsolete tcl3dOglGetFuncSignatureList procedure.

See also: tcl3dOglGetFuncList
tcl3dOglGetFuncVersion
tcl3dOglGetFuncDeprecated
tcl3dOglGetUrl

Name: tcl3dOglGetFuncVersion - Get the version or extension name of an OpenGL function.

Synopsis: tcl3dOglGetFuncVersion { func }

Description: Return the version or extension name of OpenGL function "func" as a string.
If "func" is not contained in the list of wrapped OpenGL functions (see tcl3dOglGetFuncList), an empty string is returned.

Note: This procedure replaces the obsolete tcl3dOglGetFuncVersionList procedure.

See also: tcl3dOglGetFuncList
tcl3dOglGetFuncSignature
tcl3dOglGetFuncDeprecated
tcl3dOglGetUrl
tcl3dOglGetEnumVersion

Name: tcl3dOglGetEnumVersion - Get the version or extension name of an OpenGL enumeration.

Synopsis: `tcl3dOglGetEnumVersion { enum }`

Description: Return the version or extension name of OpenGL enumeration "enum" as a string. If "enum" is not a wrapped OpenGL enumeration, an empty string is returned.

See also: `tcl3dOglGetVersionList`
`tcl3dOglGetVersionFuncs`
`tcl3dOglGetVersionEnums`
`tcl3dOglGetFuncVersion`

Name: `tcl3dOglGetFuncDeprecated` - Get the OpenGL version, an OpenGL function has been declared deprecated.

Synopsis: `tcl3dOglGetFuncDeprecated { func }`

Description: Return the version when OpenGL function "func" has been declared deprecated. The result is in the format "3.1", "3.2". For non-deprecated functions "0.0" is returned.

If "func" is not contained in the list of wrapped OpenGL functions (see `tcl3dOglGetFuncList`), an empty string is returned.

See also: `tcl3dOglGetFuncList`
`tcl3dOglGetFuncSignature`
`tcl3dOglGetFuncVersion`
`tcl3dOglGetUrl`

Name: `tcl3dOglGetUrl` - Get the URL of the official documentation of an OpenGL item.

Synopsis: `tcl3dOglGetUrl { item }`

Description: Return the URL of the official documentation of OpenGL item "item" as a string. Item can be the name of a function, extension or enumeration. If no documentation page exists, a Google search URL for that item is returned.

Note: The documentation pages on www.opengl.org currently only include OpenGL up to version 2.1.

See also: `tcl3dOglGetFuncList`
`tcl3dOglGetUrl`
`tcl3dOglGetVersionFuncs`
`tcl3dOglGetVersionEnums`

Name: `tcl3dOglGetVersionFuncs` - Get the function names of an OpenGL version or extension.

Synopsis: `tcl3dOglGetVersionFuncs { version }`

Description: Return the function names of OpenGL version or extension "version" as a list. If "version" is not a supported version or extension, an empty list is returned.

See also: `tcl3dOglGetFuncList`
`tcl3dOglGetVersionList`
`tcl3dOglGetFuncVersion`
`tcl3dOglGetVersionEnums`

Name: `tcl3dOglGetVersionEnums` - Get the enumeration names of

an OpenGL version or extension.

Synopsis: `tcl3dOglGetVersionEnums { version }`

Description: Return the enumeration names of OpenGL version or extension "version" as a list. If "version" is not a supported version or extension, an empty list is returned.

See also: `tcl3dOglGetFuncList`
`tcl3dOglGetVersionList`
`tcl3dOglGetEnumVersion`
`tcl3dOglGetVersionFuncs`

Implementation file: tcl3dOglQuery.tcl

Copyright: 2007-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dOglQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the OpenGL module.

Name: tcl3dOglGetVersion - Get OpenGL version string.

Synopsis: tcl3dOglGetVersion {}

Description: Return the version string of the wrapped OpenGL library. The version string does not have a specific format. It depends on the vendor of the OpenGL implementation. Some examples:
 1.2 APPLE-1.4.56
 2.1.2 NVIDIA 173.14.12

If no OpenGL context has been established (i.e. a Togl window has not been created), the function returns an empty string.

See also: tcl3dOglGetVersions
 tcl3dGetLibraryInfo
 tcl3dOglHaveVersion

Name: tcl3dOglGetGlewVersion - Get GLEW version string.

Synopsis: tcl3dOglGetGlewVersion {}

Description: Return the version string of the GLEW wrapper library. The version is returned as "Major.Minor.Patch".

If no OpenGL context has been established (i.e. a Togl window has not been created), the function returns an empty string.

See also: tcl3dOglGetVersion
 tcl3dOglGetVersions

Name: tcl3dOglHaveFunc - Check availability of a specific OpenGL function.

Synopsis: tcl3dOglHaveFunc { glFuncName }

Description: glFuncName : string

Return 1, if the OpenGL function "glFuncName" is provided by the underlying OpenGL implementation. Otherwise return 0.

Example: tcl3dOglHaveFunc glGenQueriesARB
 checks the availability of the occlusion query related ARB extension function glGenQueriesARB.

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to this function.

See also: `tcl3dOglHaveExtension`

Name: `tcl3dOglHaveExtension` - Check availability of a specific OpenGL extension.

Synopsis: `tcl3dOglHaveExtension { extensionName }`

Description: `extensionName` : string

Return 1, if the OpenGL extension "extensionName" is provided by the underlying OpenGL implementation. Otherwise return 0.

Example: `tcl3dOglHaveExtension GL_ARB_multitexture` checks the availability of the multitexturing extension.

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to this function.

See also: `tcl3dOglGetExtensions`

Name: `tcl3dOglHaveVersion` - Check availability of a specific OpenGL version.

Synopsis: `tcl3dOglHaveVersion { majorWanted { minorWanted 0 } { patchWanted 0 } }`

Description: `majorWanted` : int
`minorWanted` : int
`patchWanted` : int

Description: Return 1, if the OpenGL version fits the supplied major, minor and patch level numbers. Otherwise return 0.

Note: The version number of the OpenGL implementation is extracted from the string returned by calling "glGetString GL_VERSION". As some vendors format the version in an unusual way, this function may not work correctly on all platforms.

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to this function.

See also: `tcl3dOglGetVersions`

Name: `tcl3dOglGetVersions` - Get OpenGL version information.

Synopsis: `tcl3dOglGetVersions {}`

Description: Return OpenGL version information as a list of (key,value) pairs. Keys are the following OpenGL version types: `GL_VENDOR`, `GL_RENDERER`, `GL_VERSION`, `GLU_VERSION`, `GL_SHADING_LANGUAGE_VERSION`, `GLEW_VERSION`. Values are the corresponding version strings as returned by the underlying OpenGL implementation.

Example:

```
{GL_VENDOR {Intel Inc.}}
{GL_RENDERER {Intel GMA 950 OpenGL Engine}}
{GL_VERSION {1.2 APPLE-1.4.56}}
{GLU_VERSION {1.3 MacOSX}}
```

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to

this function.

See also: `tcl3dOglHaveVersion`
`tcl3dOglGetExtensions`

Name: `tcl3dOglGetExtensions` - Get all supported OpenGL extensions.

Synopsis: `tcl3dOglGetExtensions { }`

Description: Return a two-element list containing OpenGL extension information. The first sub-list contains all OpenGL extensions, the second sub-list contains all GLU extensions supported by the OpenGL implementation.

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to this function.

See also: `tcl3dOglHaveExtension`
`tcl3dOglGetVersions`

Name: `tcl3dOglGetIntState` - Get OpenGL state variable.

Synopsis: `tcl3dOglGetIntState { state { numVals 1 } }`

Description: `state` : GLenum
`numVals` : int

Utility function to query an integer OpenGL state variable with `glGetIntegerv`. The state variable to be queried is specified as an GLenum in parameter "state".

The value of the state variable is returned as an integer scalar value, if "numVals" is 1. If "numVals" is greater than 1, a Tcl list is returned.

Note: See Appendix B of the OpenGL Red Book for a list of state variables.

See also: `tcl3dOglGetFloatState`
`tcl3dOglGetDoubleState`

Name: `tcl3dOglGetFloatState` - Get OpenGL state variable.

Synopsis: `tcl3dOglGetFloatState { state { numVals 1 } }`

Description: `state` : GLenum
`numVals` : int

Utility function to query a 32-bit floating point OpenGL state variable with `glGetFloatv`. The state variable to be queried is specified as an GLenum in parameter "state".

The value of the state variable is returned as a float scalar value, if "numVals" is 1. If "numVals" is greater than 1, a Tcl list is returned.

Note: See Appendix B of the OpenGL Red Book for a list of state variables.

See also: `tcl3dOglGetIntState`
`tcl3dOglGetDoubleState`

Name: `tcl3dOglGetDoubleState` - Get OpenGL state variable.

Synopsis: `tcl3dOglGetDoubleState { state { numVals 1 } }`

Description: state : GLenum
 numVals : int

Utility function to query a 64-bit floating point OpenGL state variable with `glGetDoublev`. The state variable to be queried is specified as an GLenum in parameter "state".

The value of the state variable is returned as a double scalar value, if "numVals" is 1. If "numVals" is greater than 1, a Tcl list is returned.

Note: See Appendix B of the OpenGL Red Book for a list of state variables.

See also: tcl3dOglGetIntState
 tcl3dOglGetFloatState

Name: tcl3dOglGetMaxTextureSize - Get maximum texture size.

Synopsis: tcl3dOglGetMaxTextureSize {}

Description: Utility function to get maximum size of a texture. The maximum texture size is returned as integer value. This function corresponds to querying state variable `GL_MAX_TEXTURE_SIZE`.

See also: tcl3dOglGetIntState
 tcl3dOglGetMaxTextureUnits

Name: tcl3dOglGetMaxTextureUnits - Get maximum texture units.

Synopsis: tcl3dOglGetMaxTextureUnits {}

Description: Utility function to get maximum number of texture units. The maximum number of texture units is returned as an integer value. This function corresponds to querying state variable `GL_MAX_TEXTURE_UNITS`.

See also: tcl3dOglGetIntState
 tcl3dOglGetMaxTextureSize

Name: tcl3dOglGetViewport - Get current viewport.

Synopsis: tcl3dOglGetViewport {}

Description: Utility function to get the current viewport. The viewport is returned as a 4-element Tcl list: { LowerLeftX LowerLeftY Width Height } This function corresponds to querying state variable `GL_VIEWPORT`.

See also: tcl3dOglGetIntState

Name: tcl3dOglGetShaderInfoLog - Get shader object log.

Synopsis: tcl3dOglGetShaderInfoLog { shader }

Description: shader : Shader object

Utility function for easier use of OpenGL function `glGetShaderInfoLog`. Given the shader object (as returned by function `glCreateShader`), the function returns the information log message as a Tcl string.

See also: `tcl3dOglGetProgramInfoLog`
`tcl3dOglGetShaderSource`
`tcl3dOglGetInfoLogARB`

Name: `tcl3dOglGetProgramInfoLog` - Get shader program log.

Synopsis: `tcl3dOglGetProgramInfoLog { shader }`

Description: `shader` : Shader program

Utility function for easier use of OpenGL function `glGetProgramInfoLog`.
Given the shader program (as returned by function `glCreateProgram`), the function returns the information log message as a Tcl string.

See also: `tcl3dOglGetShaderInfoLog`
`tcl3dOglGetShaderSource`
`tcl3dOglGetInfoLogARB`

Name: `tcl3dOglGetShaderSource` - Get shader object source.

Synopsis: `tcl3dOglGetShaderSource { shader }`

Description: `shader` : Shader object

Utility function for easier use of OpenGL function `glGetShaderSource`.
Given the shader object (as returned by function `glCreateShader`), the function returns the shader source code as a Tcl string.

See also: `tcl3dOglGetShaderInfoLog`
`tcl3dOglGetProgramInfoLog`
`tcl3dOglGetInfoLogARB`

Name: `tcl3dOglGetInfoLogARB` - Get shader object log.

Synopsis: `tcl3dOglGetInfoLogARB { object }`

Description: `object` : Shader object

Utility function for easier use of OpenGL function `glGetInfoLogARB`.
Given the shader object (as returned by function `glCreateProgramObjectARB`), the function returns the information log message as a Tcl string.

See also: `tcl3dOglGetShaderInfoLog`
`tcl3dOglGetProgramInfoLog`
`tcl3dOglGetShaderSource`

Name: `tcl3dOglGetExtSuffixes` - Get OpenGL extension suffixes.

Synopsis: `tcl3dOglGetStates {}`

Description: Return a list of all OpenGL extension suffixes.
Currently these are:
"ARB" "EXT" "NV" "ATI" "SGI" "SGIX" "SGIS"
"SUN" "WIN" "MESA" "INTEL" "IBM" "HP"

See also: `tcl3dOglGetExtensions`

Name: `tcl3dOglFindFunc` - Find an OpenGL function.

Synopsis: `tcl3dOglFindFunc { glFunc }`

Description: Return the name of an OpenGL function implemented in the available OpenGL driver. First it is checked, if the function is available as a native implementation. If the OpenGL version does not supply the function, all possible extension names are checked in the order as returned by `tcl3dOglGetExtSuffixes`. If none of these checks succeed, an empty string is returned.

See also: `tcl3dOglGetExtSuffixes`

Name: `tcl3dOglGetStates` - Get OpenGL state variables.

Synopsis: `tcl3dOglGetStates { {sortFlag "none"} }`

Description: `sortFlag : string (increasing|decreasing|none)`

Query all state variables of the OpenGL library and return the results as a list of sub-lists. Each sublist contains a flag indicating the success of the query, the query command used, the key and the value(s).

Note: This function is still incomplete. Chances are high, it will never be finished.

This function has been declared obsolete with Tcl3D version 0.4.2.

See also: `tcl3dOglGetExtensions`
`tcl3dOglGetVersions`

Implementation file: tcl3dOglUtil.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dOglUtil.tcl

Author: Paul Obermeier

Description: Tcl module with miscellaneous utility procedures related to the OpenGL module.

Name: tcl3dOglExtInit - Initialize the extension library.

Synopsis: tcl3dOglExtInit {}

Description: Initialize the OpenGL extension library. If no OpenGL context has been established (i.e. a Togl window has not been created), the function throws an error. It is recommended to add a call to tcl3dOglExtInit in the create callback. Note: With Tcl3D versions starting at 0.4, this procedure is not needed anymore, because the GLEW extension functions are initialized within the Togl widget start-up code. You may leave it in your code however for backwards compatibility.

See also:

Name: glMultiDrawElements - Draw multiple array elements.

Synopsis: glMultiDrawElements {
 mode count type indices primcount }

Description: mode : GLenum
 count : tcl3dVector of type GLuint
 type : GLenum
 indices : List of tcl3dVectors
 primcount : integer

Tcl wrapper for the OpenGL function glMultiDrawElements. As the Tcl3D Swig wrapper currently does not support "void **" pointers, the multiple array elements must be specified as a list of tcl3dVectors.

See also:

Name: tcl3dOglGetError - Check for an OpenGL error.

Synopsis: tcl3dOglGetError {}

Description: Check, if an OpenGL related error has been occurred. If no error occurred, an empty string is returned. Otherwise a formatted string showing the error number and the error message is returned.

See also:

Name: tcl3dOglShaderSource - Wrapper for glShaderSource.

Synopsis: `tcl3dOglShaderSource { shaderId shaderString }`

Description: `shaderId` : Shader handle
`shaderString` : string

Wrapper for easier use of OpenGL function `glShaderSource`. In contrast to `glShaderSource` only the shader program identifier (created with a call to `glCreateShaderObject`) and the shader source have to be specified.

See also:

Name: `tcl3dOglSetNormalMode` - Set the execution mode of OpenGL functions to normal.

Synopsis: `tcl3dOglSetNormalMode { { printCmd puts } }`

Description: `printCmd` : command name

Set the execution mode of all OpenGL functions to normal.

The "printCmd" will be used to output OpenGL command execution infos. If not specified, the information is printed onto stdout with the puts command. The printCmd must be a command with a single string parameter.

See the documentation of `tcl3dOglSetMode` for a description of the OpenGL execution modes.

See also: `tcl3dOglSetSafeMode`
`tcl3dOglSetDebugMode`
`tcl3dOglSetMode`

Name: `tcl3dOglSetSafeMode` - Set the execution mode of OpenGL functions to safe.

Synopsis: `tcl3dOglSetSafeMode { { printCmd puts } }`

Description: `printCmd` : command name

Set the execution mode of all OpenGL functions to safe.

The "printCmd" will be used to output OpenGL command execution infos. If not specified, the information is printed onto stdout with the puts command. The printCmd must be a command with a single string parameter.

See the documentation of `tcl3dOglSetMode` for a description of the OpenGL execution modes.

See also: `tcl3dOglSetNormalMode`
`tcl3dOglSetDebugMode`
`tcl3dOglSetMode`

Name: `tcl3dOglSetDebugMode` - Set the execution mode of OpenGL functions to debug.

Synopsis: `tcl3dOglSetDebugMode { { printCmd puts } }`

Description: `printCmd` : command name

Set the execution mode of all OpenGL functions to debug.

The "printCmd" will be used to output OpenGL command execution infos. If not specified, the information is printed onto stdout with the puts command. The printCmd must be a command with a single string

parameter.

See the documentation of `tcl3dOglSetMode` for a description of the OpenGL execution modes.

See also: `tcl3dOglSetNormalMode`
`tcl3dOglSetSafeMode`
`tcl3dOglSetMode`

Name: `tcl3dOglSetMode` - Set the execution mode for OpenGL functions.

Synopsis: `tcl3dOglSetMode { mode { printCmd puts } }`

Description: `mode` : string
`printCmd` : command name

The OpenGL core and extension functions can be used in 3 different modes:
"normal", "safe", "debug".

`normal`: Use the OpenGL functions as wrapped by SWIG. This is the fastest mode. If using an OpenGL function not available in the used driver implementation, this mode will dump core.
`safe`: In this mode every OpenGL function is checked for availability in the driver before execution. If it's not available, a message is printed out.
`debug`: This mode checks the availability of an OpenGL function like the safe mode, and additionally prints out every OpenGL function before execution.

The "printCmd" will be used to output OpenGL command execution infos. If not specified, the information is printed onto stdout with the puts command. The printCmd must be a command with a single string parameter.

See also: `tcl3dOglSetNormalMode`
`tcl3dOglSetSafeMode`
`tcl3dOglSetDebugMode`

Implementation file: tcl3dOsgBitmaps.tcl

Copyright: 2009-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOsg
Filename: tcl3dOsgBitmaps.tcl

Author: Paul Obermeier

Description: Tcl module with bitmaps specific to the OSG module.

Name: tcl3dOsgGetBitmap - Get the bitmap image of a node type.

Synopsis: tcl3dOsgGetBitmap { nodeType }

Description: Get the bitmap image of a node type. If the node type is not known or no bitmap is available yet, a bitmap with a question mark is returned.

See also: tcl3dOsgGetBitmapName

Implementation file: tcl3dOsgKeysym.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOsg
Filename: tcl3dOsgKeysym.tcl

Author: Paul Obermeier

Description: Tcl module for mapping keysym values.
Taken from Wiki page <http://wiki.tcl.tk/13162>.

Name: tcl3dOsgKeysym - Convert a keysym into decimal and vice versa.

Synopsis: tcl3dOsgKeysym { key }

Description: Convert a Tk keysym into it's decimal value and vice versa.
Example:
tcl3dOsgKeysym A --> 65
tcl3dOsgKeysym 65 --> A

See also:

Implementation file: tcl3dOsgQuery.tcl

Copyright: 2009-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOsg
Filename: tcl3dOsgQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the OSG module.

Name: tcl3dOsgGetVersion - Get OSG version string.

Synopsis: tcl3dOsgGetVersion {}

Description: Get the version of the wrapped OpenSceneGraph library. If no OpenGL context has been established (i.e. a Togl window has not been created), the function returns an empty string.

See also: tcl3dGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dOsgUtil.tcl

Copyright: 2009-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOsg
Filename: tcl3dOsgUtil.tcl

Author: Paul Obermeier

Description: Tcl module with miscellaneous Tcl3D utility procedures related to the OSG module.

Name: tcl3dOsgVecPrint - Print a OSG vector.
tcl3dOsgMatPrint - Print a OSG matrix.
tcl3dOsgBBoxPrint - Print a OSG bounding box.
tcl3dOsgBSpherePrint - Print a OSG bounding sphere.

Synopsis: tcl3dOsgVecPrint { vec { precisionString "%6.3f" } }
tcl3dOsgMatPrint { mat { precisionString "%6.3f" } }
tcl3dOsgBBoxPrint { box { precisionString "%6.3f" } }
tcl3dOsgBSpherePrint { sph { precisionString "%6.3f" } }

Description: vec : osg::Vec
mat : osg::Matrix
box : osg::BoundingBox
sph : osg::BoundingSphere
precisionString : string

Print the values of the corresponding OSG classes onto stdout. The precisionString parameter can be optionally specified and must supply a format specification in a C-printf style.

See also:

Name: tcl3dOsgVecArrayPrint - Print an array of vectors.
tcl3dOsgScalarArrayPrint - Print an array of scalars.
tcl3dOsgObjectArrayPrint - Print an array of objects.

Synopsis: tcl3dOsgVecArrayPrint { arr { precisionString "%6.3f" } }
tcl3dOsgScalarArrayPrint { arr { precisionString "%6.3f" } }
tcl3dOsgObjectArrayPrint { arr { precisionString "%s" } }

Description: arr : osg::VecArray, std::vector, osg::MixinVector
precisionString : string

Print the values of all elements of container "arr". "arr" can be either a osg::VecArray, a std::vector or a osg::MixinVector container. Depending on the element type, special functions are available: tcl3dOsgVecArrayPrint prints the value of all osg::Vec's contained in the array. tcl3dOsgScalarArrayPrint prints the value of all scalars contained in the array. tcl3dOsgObjectArrayPrint prints the name of all osg::Object's contained in the array.

The precisionString parameter can be optionally specified and must supply a format specification in a C-printf style.

See also: tcl3dOsgScalarArrayPrint

Name: tcl3dOsgGetVisitorTypeName - Get visitor type name.

Synopsis: tcl3dOsgGetVisitorTypeName { visitorType }

Description: visitorType : int

 Return the string representation of a
 osg::NodeVisitor::VisitorType enumeration type.

See also: tcl3dOsgGetTraversalModeName

Name: tcl3dOsgGetTraversalModeName - Get traversal mode name.

Synopsis: tcl3dOsgGetTraversalModeName { travMode }

Description: travMode : int

 Return the string representation of a
 osg::NodeVisitor::TraversalMode enumeration type.

See also: tcl3dOsgGetVisitorTypeName

Name: tcl3dOsgSendButtonPress
 tcl3dOsgSendButtonRelease
 tcl3dOsgSendMouseMotion
 tcl3dOsgSendKeyPress
 tcl3dOsgSendKeyRelease
 tcl3dOsgSendWindowResize
 - Send the corresponding event down to OSG.

Synopsis: tcl3dOsgSendButtonPress { osgwin x y buttonNum }
 tcl3dOsgSendButtonRelease { osgwin x y buttonNum }
 tcl3dOsgSendMouseMotion { osgwin x y }
 tcl3dOsgSendKeyPress { osgwin key }
 tcl3dOsgSendKeyRelease { osgwin key }
 tcl3dOsgSendWindowResize { osgwin w h }

Description: osgwin : int
 x, y : int (cursor position)
 w, h : int (window width and height)
 buttonNum : int (Button number)
 key : int (KeySym)

 tcl3dOsgSend* procedures transfer a Tcl/Tk event down
 to OSG. Note, that no redraw is done. You must either
 use "after idle" with a postredisplay command or use
 the utility commands without the "Send" in the name.

See also:

Name: tcl3dOsgAddTrackballBindings
 - Add OS independent mouse bindings for trackball usage.

Synopsis: tcl3dOsgAddTrackballBindings { toglwin osgwin }

Description: toglwin : Togl window identifier
 osgwin : int

See also:

Implementation file: tcl3dSDLQuery.tcl

Copyright: 2007-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dSDL
Filename: tcl3dSDLQuery.tcl

Author: Paul Obermeier

Description: Tcl module with query procedures related to the SDL module.

Name: tcl3dSDLGetVersion - Get SDL version string.

Synopsis: tcl3dSDLGetVersion {}

Description: Return the version string of the wrapped SDL library. The version is returned as "Major.Minor.Patch".

See also: tcl3dOglGetVersions
tcl3dGetLibraryInfo

Implementation file: tcl3dSDLUtil.tcl

```

Copyright:      2006-2010 Paul Obermeier (obermeier@tcl3d.org)

                See the file "Tcl3D_License.txt" for information on
                usage and redistribution of this file, and for a
                DISCLAIMER OF ALL WARRANTIES.

Module:         Tcl3D -> tcl3dSDL
Filename:       tcl3dSDLUtil.tcl

Author:        Paul Obermeier

Description:    Tcl module with miscellaneous utility
                procedures related to the SDL module.

Name:          tcl3dSDLGetFocusName - Convert focus state bitfield.

Synopsis:      tcl3dSDLGetFocusName { state }

Description:    state : int

                Return a SDL focus state bitfield as the corresponding
                string representation.
                See file SDL_active.h for the definition of possible
                bitfield values.

See also:      tcl3dSDLGetButtonName
                tcl3dSDLGetHatName
                tcl3dSDLGetEventName

Name:          tcl3dSDLGetButtonName - Convert button state bitfield.

Synopsis:      tcl3dSDLGetButtonName { state }

Description:    state : int

                Return a SDL button state bitfield as the corresponding
                string representation.
                See file SDL_mouse.h for the definition of possible
                bitfield values.

See also:      tcl3dSDLGetFocusName
                tcl3dSDLGetHatName
                tcl3dSDLGetEventName

Name:          tcl3dSDLGetHatName - Convert hat state bitfield.

Synopsis:      tcl3dSDLGetHatName { state }

Description:    state : int

                Return a SDL hat state bitfield as the corresponding
                string representation.
                See file SDL_joystick.h for the definition of possible
                bitfield values.

See also:      tcl3dSDLGetFocusName
                tcl3dSDLGetButtonName
                tcl3dSDLGetEventName

Name:          tcl3dSDLGetEventName - Convert event enumeration.

Synopsis:      tcl3dSDLGetEventName { state }

Description:    state : int (SDL event enumeration)

```

Return SDL event related enumeration as the corresponding string representation. See file `SDL_events.h` for the definition of possible enumeration values.

See also: `tcl3dSDLGetFocusName`
`tcl3dSDLGetButtonName`
`tcl3dSDLGetHatName`

Name: `tcl3dSDLFrames2MSF` - Convert CD frames.

Synopsis: `tcl3dSDLFrames2MSF { frames }`

Description: `frames : int`

Return CD frame as minutes/seconds/frames as a list of 3 integers.

See also:

Name: `tcl3dSDLGetTrackTypeName` - Convert track type bitfield.

Synopsis: `tcl3dSDLGetTrackTypeName { type }`

Description: `type : int`

Return SDL CD track type bitfield as the corresponding string representation. See file `SDL_cdrom.h` for the definition of possible bitfield values.

See also: `tcl3dSDLGetCdStatusName`

Name: `tcl3dSDLGetCdStatusName` - Convert CD status enumeration.

Synopsis: `tcl3dSDLGetCdStatusName { status }`

Description: `status : int (CD status enumeration)`

Return SDL CD status enumeration as the corresponding string representation. See file `SDL_cdrom.h` for the definition of possible enumeration values (`CDstatus`).

See also: `tcl3dSDLGetTrackTypeName`

Implementation file: tcl3dUtilCapture.tcl

```

Copyright:      2005-2010 Paul Obermeier (obermeier@tcl3d.org)

                See the file "Tcl3D_License.txt" for information on
                usage and redistribution of this file, and for a
                DISCLAIMER OF ALL WARRANTIES.

Module:         Tcl3D -> tcl3dOgl
Filename:       tcl3dUtilCapture.tcl

Author:        Paul Obermeier

Description:    Tcl module implementing functions for capturing window
                contents into an image or file.
                Note: All of the functionality requires the help of the
                Img extension. Some of the functionality requires the
                help of the Twapi extension and is therefore only
                available on Windows.

Name:          tcl3dWidget2Img - Copy widget content into photo image.

Synopsis:      tcl3dWidget2Img { win { ign "" } }

Description:   win : string (Widget name)
                ign : string

                Copy contents of widget "win" and all of its
                sub-widgets into a photo image.
                If "ign" is specified and not the empty string, it is
                interpreted as a pattern for widget names, that should
                be ignored while traversing the widget hierarchy.
                The pattern is passed to the "string match" command.

                Return the photo image identifier.

See also:      tcl3dWidget2File
                tcl3dCanvas2Img
                tcl3dClipboard2Img
                tcl3dWindow2Img

Name:          tcl3dWidget2File - Copy widget content into image file.

Synopsis:      tcl3dWidget2File { win fileName { ign "" }
                { fmt "JPEG" } { opts "" } }

Description:   win      : string (Widget name)
                fileName : string
                ign      : string
                fmt      : string
                opts     : string

                Copy contents of widget "win" and all of its
                sub-widgets into a photo image and save this image to
                file "fileName". The file format handler is determined
                with "fmt". Some formats need optional parameters.
                These can be supplied in "opts".
                See the Img documentation (man img) for a list of format
                handlers and options.
                If "ign" is specified and not the empty string, it is
                interpreted as a pattern for widget names, that should
                be ignored while traversing the widget hierarchy.
                The pattern is passed to the "string match" command.

See also:      tcl3dWidget2Img
                tcl3dCanvas2File
                tcl3dClipboard2File
                tcl3dWindow2File

```

Name: tcl3dCanvas2Img - Copy canvas content into photo image.

Synopsis: tcl3dCanvas2Img { canv }

Description: canv : string (Widget name)

Copy the contents of canvas "canv" into a photo image.

Return the photo image identifier.

See also: tcl3dCanvas2File
tcl3dWidget2Img
tcl3dClipboard2Img
tcl3dWindow2Img

Name: tcl3dCanvas2File - Copy canvas content into image file.

Synopsis: tcl3dCanvas2File { canv fileName { fmt "JPEG" }
{ opts "" } }

Description: canv : string (Widget name)
fileName : string
fmt : string
opts : string

Copy the contents of canvas "canv" into a photo image and save the image to file "fileName". The file format handler is determined with "fmt". Some formats need optional parameters. These can be supplied in "opts". See the Img documentation (man img) for a list of format handlers and options.

See also: tcl3dCanvas2Img
tcl3dWidget2File
tcl3dClipboard2File
tcl3dWindow2File

Name: tcl3dClipboard2Img - Copy clipboard content into photo image.

Synopsis: tcl3dClipboard2Img {}

Description: Copy the contents of the Windows clipboard into a photo image.

Return the photo image identifier, if successful. Otherwise a Tcl error is thrown.

Note: This function is currently available only under Windows and needs the Twapi extension.

See also: tcl3dClipboard2File
tcl3dWidget2Img
tcl3dCanvas2Img
tcl3dWindow2Img

Name: tcl3dClipboard2File - Copy clipboard content into file.

Synopsis: tcl3dClipboard2File { fileName { fmt "JPEG" }
{ opts "" } }

Description: fileName : string
fmt : string
opts : string

Copy the contents of the Windows clipboard into a photo image and save the image to file "fileName". The file format handler is determined with "fmt". Some formats

need optional parameters.
 These can be supplied in "opts".
 See the Img documentation (man img) for a list of format
 handlers and options.

Note: This function is currently available only under
 Windows and needs the Twapi extension.

See also: tcl3dClipboard2Img
 tcl3dWidget2File
 tcl3dCanvas2File
 tcl3dWindow2File

Name: tcl3dImg2Clipboard - Copy photo image into clipboard.

Synopsis: tcl3dImg2Clipboard { phImg }

Description: phImg : string (Photo image identifier)

Copy photo image "phImg" into the Windows clipboard.

Note: This function is currently available only under
 Windows and needs the Twapi extension.

See also: tcl3dClipboard2Img

Name: tcl3dWindow2Clipboard - Copy window contents into
 clipboard.

Synopsis: tcl3dWindow2Clipboard {}

Description: Copy the contents of the top level window (Alt-PrtSc)
 into the Windows clipboard.

Note: This function is currently available only under
 Windows and needs the Twapi extension.

See also: tcl3dClipboard2Img

Name: tcl3dDesktop2Clipboard - Copy desktop contents into
 clipboard.

Synopsis: tcl3dDesktop2Clipboard {}

Description: Copy the contents of the whole desktop (PrtSc) into the
 Windows clipboard.

Note: This function is currently available only under
 Windows and needs the Twapi extension.

See also: tcl3dWindow2Clipboard

Name: tcl3dWindow2Img - Copy window contents into photo image.

Synopsis: tcl3dWindow2Img {}

Description: Copy the contents of the top level window into a photo
 image.

Return the photo image identifier, if successful.
 Otherwise a Tcl error is thrown.

See also: tcl3dWindow2File

Name: tcl3dWindow2File - Copy window contents into file.

Synopsis: tcl3dWindow2File { fileName { fmt "JPEG" } { opts "" } }

Description: fileName : string
 fmt : string
 opts : string

Copy the contents of the top level window into a photo image and save the image to file "fileName". The file format handler is determined with "fmt". Some formats need optional parameters. These can be supplied in "opts". See the Img documentation (man img) for a list of format handlers and options.

See also: tcl3dWindow2Img

Implementation file: tcl3dUtilColors.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
Filename: tcl3dUtilColors.tcl

Author: Paul Obermeier, Victor G. Bonilla

Description: Tcl module to convert Tcl color names into Tcl3D color lists. Color names may be specified as numeric values or strings.
Currently accepted Tcl color names:
#RRGGBB
All names as listed in the Tcl manual pages, section colors.

This module has been inspired by Victor G. Bonilla, who wrote the first version of this file.

Name: tcl3dGetColorNames - Get all supported Tcl color names.

Synopsis: tcl3dGetColorNames {}

Description: Return a list of all supported Tcl color name strings.

See also: tcl3dFindColorName

Name: tcl3dFindColorName - Validate Tcl color name.

Synopsis: tcl3dFindColorName { colorName }

Description: colorName : string
Check, if supplied color name is a valid string color name. If true, return the supplied color name, otherwise return an empty string.

See also: tcl3dGetColorNames

Name: tcl3dName2Hex - Convert color name to Tcl hexadecimal.

Synopsis: tcl3dName2Hex { colorName }

Description: colorName : string
Convert Tcl color name "colorName" into the corresponding Tcl hexadecimal representation.
Tcl colors are returned as string in the following format:
#RRGGBB

See also: tcl3dName2rgb
tcl3dName2rgbf

Name: tcl3dName2Hexa - Convert color name to Tcl hexadecimal.

Synopsis: tcl3dName2Hexa { colorName }

Description: colorName : string
Convert Tcl color name "colorName" into the corresponding Tcl hexadecimal representation.
Tcl colors are returned as string in the following format:

```
#RRGGBBAA
```

See also: `tcl3dName2rgba`
`tcl3dName2rgbaf`

Name: `tcl3dName2rgb` - Convert color name to OpenGL RGB.

Synopsis: `tcl3dName2rgb { colorName }`

Description: `colorName` : string

Convert Tcl color name "colorName" into the corresponding OpenGL RGB representation.
OpenGL colors are returned as a list of 3 unsigned bytes: { r g b }

See also: `tcl3dName2rgba`
`tcl3dName2rgbfb`

Name: `tcl3dName2rgbfb` - Convert color name to OpenGL float RGB.

Synopsis: `tcl3dName2rgbfb { colorName }`

Description: `colorName` : string

Convert Tcl color name "colorName" into the corresponding OpenGL float RGB representation.
OpenGL colors are returned as a list of 3 floats in the range [0..1]: { r g b }

See also: `tcl3dName2rgbaf`
`tcl3dName2rgb`

Name: `tcl3dName2rgba` - Convert color name to OpenGL RGBA.

Synopsis: `tcl3dName2rgba { colorName }`

Description: `colorName` : string

Convert Tcl color name "colorName" into the corresponding OpenGL RGBA representation.
OpenGL colors are returned as a list of 4 unsigned bytes: { r g b a }

See also: `tcl3dName2rgb`
`tcl3dName2rgbaf`

Name: `tcl3dName2rgbaf` - Convert color name to OpenGL float RGBA.

Synopsis: `tcl3dName2rgbaf { colorName }`

Description: `colorName` : string

Convert Tcl color name "colorName" into the corresponding OpenGL float RGBA representation.
OpenGL colors are returned as a list of 4 floats in the range [0..1]: { r g b a }

See also: `tcl3dName2rgba`
`tcl3dName2rgbfb`

Name: `tcl3dRgb2Name` - Convert OpenGL RGB to color name.

Synopsis: `tcl3dRgb2Name { r g b }`

Description: `r, g, b` : int

Convert an OpenGL RGB color representation into a hexadecimal Tcl color name string.
OpenGL colors are specified as unsigned bytes in the range [0..255].

Note: For performance issues no range checking is performed.
If specifying color values outside the allowed range, the resulting Tcl color name may result in an error like following:
can't parse color "#FD109142"

See also: tcl3dName2rgb
tcl3dRgba2Name

Name: tcl3dRgba2Name - Convert OpenGL RGBA to color name.

Synopsis: tcl3dRgba2Name { r g b a }

Description: r, g, b, a : int

Convert an OpenGL RGBA color representation into a hexadecimal Tcl color name string.
OpenGL colors are specified as unsigned bytes in the range [0..255].

Note: For performance issues no range checking is performed.
If specifying color values outside the allowed range, the resulting Tcl color name may result in an error like following:
can't parse color "#FD109142"

See also: tcl3dName2rgba
tcl3dRgb2Name

Name: tcl3dRgbf2Name - Convert OpenGL RGB to color name.

Synopsis: tcl3dRgbf2Name { r g b }

Description: r, g, b : float

Convert an OpenGL RGB color representation into a hexadecimal Tcl color name string.
OpenGL colors are specified as floats in the range [0..1].

Note: For performance issues no range checking is performed.
If specifying color values outside the allowed range, the resulting Tcl color name may result in an error like following:
can't parse color "#FD109142"

See also: tcl3dName2rgbf
tcl3dRgbf2Name

Name: tcl3dRgbuf2Name - Convert OpenGL RGBA to color name.

Synopsis: tcl3dRgbuf2Name { r g b a }

Description: r, g, b, a : float

Convert an OpenGL RGBA color representation into a hexadecimal Tcl color name string.
OpenGL colors are specified as floats in the range [0..1].

Note: For performance issues no range checking is

performed.

If specifying color values outside the allowed range, the resulting Tcl color name may result in an error like following:
can't parse color "#FD109142"

See also: tcl3dName2rgbaf
 tcl3dRgbaf2Name

Implementation file: tcl3dUtilFile.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dUtilFile.tcl

Author: Paul Obermeier

Description: Tcl module with file handling Tcl3D utility procedures.

Name: tcl3dGetTmpDir - Get the name of a temporary directory.

Synopsis: tcl3dGetTmpDir {}

Description: Return the location of a temporary directory name. The function checks the following environment variables first: TMP, TEMP, TMPDIR. If none of these variables are defined, standard places are checked (C:/Windows/Temp, /tmp).

See also: tcl3dCreateTmpDir

Name: tcl3dCreateTmpDir - Create a unique temporary directory.

Synopsis: tcl3dCreateTmpDir {}

Description: Create a unique temporary directory. Return the full path name of the created directory. The new directory is created in the standard temporary directory as returned by tcl3dGetTmpDir.

See also: tcl3dGetTmpDir

Name: tcl3dGenExtName - Create a name on the file system.

Synopsis: tcl3dGenExtName { fileName }

Description: fileName : string

Return a valid path name on the file system generated from the file name specified in "fileName". Use this function, if writing to a file from a script, which may be running from within a Starpack. If the script is not executed from a Starpack, the function returns the supplied parameter unchanged.

See also: tcl3dGetExtFile

Name: tcl3dGetExtFile - Get a name on the file system.

Synopsis: tcl3dGetExtFile { fileName }

Description: fileName : string

Return a valid path name on the file system generated from the file name specified in "fileName". Use this function, if a file is needed for reading from an external Tcl3D library, like font files used by FTGL, and the script may be executed from within a virtual file system (ex. starkit vfs or zvfs). The file included in the virtual file system is transparently copied onto the file system and that path

name is returned.
The path name is built using a system-wide temporary directory as returned by `tcl3dGetTmpDir`.
If the script is not executed from within a virtual file system, the function returns the supplied parameter unchanged.

See also: `tcl3dGenExtName`
`tcl3dGetTmpDir`

Name: `tcl3dGetDirList` - Get the contents of a directory.

Synopsis: `tcl3dGetDirList {dirName
 {showDirs 1} {showFiles 1}
 {showHiddenDirs 1} {showHiddenFiles 1}
 {dirPattern *} {filePattern *}}`

Description: `dirName` : string
`showDirs` : bool
`showFiles` : bool
`showHiddenDirs` : bool
`showHiddenFiles` : bool
`dirPattern` : string
`filePattern` : string

Scan directory "dirName" and return a two-element list consisting of all directories and files of the scanned directory.

The first element contains the directory list, where the pathnames of the directories are absolute paths.

The second element contains the file list with no path information.

The result list can be filtered by specifying the other procedure parameters and should be self-explaining.

See also: `tcl3dCreateTmpDir`

Implementation file: tcl3dUtilInfo.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dUtilInfo.tcl

Author: Paul Obermeier

Description: Tcl module to get Tcl3D related information:
 Version, extensions, state variables.

Name: tcl3dHavePackage - Check availability of a specific
 Tcl3D package.

Synopsis: tcl3dHavePackage { pkgName version }

Description: pkgName : string
 version : string

Return 1, if Tcl package "pkgName" is available in at
 least version "version". Otherwise return 0.

Example: tcl3dHavePackage tcl3dcg 0.3.2
 checks availability of the tcl3dCg package in
 at least version 0.3.2.

See also: tcl3d{SubPackage}GetVersion

Name: tcl3dGetLibraryInfo - Get library version of a Tcl3D
 module.

Synopsis: tcl3dGetLibraryInfo { pkgName }

Description: pkgName : string

Return the library version corresponding to supplied
 Tcl3D package name "pkgName" as a string. If no version
 information is available, an empty string is returned.

See also: tcl3dGetPackageInfo

Name: tcl3dGetPackageInfo - Get Tcl3D package information.

Synopsis: tcl3dGetPackageInfo {}

Description: Return a list of sub-lists containing Tcl3D package
 information. Each sub-list contains the name of the
 sub-package, the availability flag (0 or 1), the
 sub-package version as well as the version of the
 wrapped library.

Example:

```
{tcl3dcg 1 0.3.3 1.5.0015}      {tcl3ddemoutil 1 0.3.3 {}}
```

```
{tcl3dftgl 1 0.3.3 2.1.2}      {tcl3dgauges 1 0.3.3 {}}
```

```
{tcl3dgl2ps 1 0.3.3 1.3.2}     {tcl3dode 1 0.3.3 0.7.0}
```

```
{tcl3dogl 1 0.3.3 {APPLE-1.4}} {tcl3dsdl 1 0.3.3 1.2.9}
```

```
{tcl3dtogl 1 0.3.3 {}}        {tcl3dutil 1 0.3.3 {}}
```

Note: A Togl window (and therefore a graphics context)
 must have been created before issuing a call to
 this function.

See also: tcl3dShowPackageInfo

Name: tcl3dShowPackageInfo - Display package information.

Synopsis: tcl3dShowPackageInfo {}

Description: Display the version info returned by tcl3dGetPackageInfo in a toplevel window.

Note: A Togl window (and therefore a graphics context) must have been created before issuing a call to this function.

See also: tcl3dGetPackageInfo

Name: tcl3dHaveCg - Check availability of tcl3dCg module.

Synopsis: tcl3dHaveCg {}

Description: Return 1, if the Cg library has been loaded successfully via the tcl3dCg module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dCgGetVersion

Name: tcl3dHaveSDL - Check availability of tcl3dSDL module.

Synopsis: tcl3dHaveSDL {}

Description: Return 1, if the SDL library has been loaded successfully via the tcl3dSDL module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dSDLGetVersion

Name: tcl3dHaveFTGL - Check availability of tcl3dFTGL module.

Synopsis: tcl3dHaveFTGL {}

Description: Return 1, if the FTGL library has been loaded successfully via the tcl3dFTGL module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dFTGLGetVersion

Name: tcl3dHaveOde - Check availability of tcl3dOde module.

Synopsis: tcl3dHaveOde {}

Description: Return 1, if the ODE library has been loaded successfully via the tcl3dOde module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dOdeGetVersion

Name: tcl3dHaveOsg - Check availability of tcl3dOsg module.

Synopsis: tcl3dHaveOsg {}

Description: Return 1, if the OSG library has been loaded successfully via the tcl3dOsg module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dOsgGetVersion

Name: tcl3dHaveGl2ps - Check availability of tcl3dGl2ps module.

Synopsis: tcl3dHaveGl2ps {}

Description: Return 1, if the GL2PS library has been loaded successfully via the tcl3dGl2ps module. Otherwise return 0.

Note: This function is only available when loading Tcl3D via a "package require tcl3d".

See also: tcl3dGetPackageInfo
tcl3dGl2psGetVersion

Implementation file: tcl3dUtilLogo.tcl

```

Copyright:      2005-2010 Paul Obermeier (obermeier@tcl3d.org)

                See the file "Tcl3D_License.txt" for information on
                usage and redistribution of this file, and for a
                DISCLAIMER OF ALL WARRANTIES.

Module:         Tcl3D -> tcl3dOgl
Filename:       tcl3dUtilLogo.tcl

Author:        Paul Obermeier

Description:    Tcl module showing the Tcl/Tk and poSoft logo.

Name:          tcl3dLogoDestroyPoSoft - Destroy poSoft logo window.

Synopsis:      tcl3dLogoDestroyPoSoft {}

Description:    Destroy a previously opened poSoft logo window.

See also:      tcl3dLogoShowPoSoft
                tcl3dLogoShowTcl

Name:          tcl3dLogoShowPoSoft - Display poSoft logo.

Synopsis:      tcl3dLogoShowPoSoft { version copyright withdrawWin }

Description:    version      : string
                copyright   : string
                withdrawWin : string (Widget name)

                Display the poSoft logo in two possible ways:
                If "withdrawWin" is set to the empty string, the logo
                is shown in a window with decoration. This may be used
                for displaying the logo as an action for an "About"
                menu entry.
                If "withdrawWin" is set to an existing window name
                (typically the name of the main application window), the
                logo window is shown without decoration as a splash
                window, which automatically disappears after a second.
                The logo window has two label widgets to display
                additional text messages, which are specified in
                "version" and "copyright".

See also:      tcl3dLogoDestroyPoSoft
                tcl3dLogoShowTcl

Name:          tcl3dLogoDestroyTcl - Destroy Tcl logo window.

Synopsis:      tcl3dLogoDestroyTcl { w img }

Description:    Destroy a previously opened Tcl logo window.

See also:      tcl3dLogoShowTcl
                tcl3dLogoShowPoSoft

Name:          tcl3dLogoShowTcl - Display Tcl logo.

Synopsis:      tcl3dLogoShowTcl { args }

Description:    args : variable parameter list

                Display the Tcl logo with additional text messages in
                a window with decoration. This may be used
                for displaying the logo as an action for an "About"
                menu entry.

```

"args" may contain any combination of the following
package names:
Tk Img Tktable combobox mysqltcl tcom

See also: `tcl3dLogoShowPoSoft`

Implementation file: tcl3dUtilTrackball.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dUtilTrackball.tcl

Author: Paul Obermeier

Description: Simple trackball-like motion adapted (ripped off) from projtex.c (written by David Yu and David Blythe). See the SIGGRAPH '96 Advanced OpenGL course notes.

Usage overview:

Call tcl3dTbInit before any other trackball call.
 Call tcl3dTbReshape from the reshape callback.
 Call tcl3dTbMatrix to get the trackball matrix rotation.
 Call tcl3dTbStartMotion to begin trackball movement.
 Call tcl3dTbStopMotion to stop trackball movement.
 Call tcl3dTbMotion from the motion callback.
 Call tcl3dTbAnimate(1) if you want the trackball to continue spinning after the mouse button has been released.
 Call tcl3dTbAnimate(0) if you want the trackball to stop spinning after the mouse button has been released.

See ftglDemo.tcl for a real world example.

Modified for Tcl3D by Paul Obermeier 2006/02/02
 See www.tcl3d.org for the Tcl3D extension.

Name: tcl3dTbStartMotion - Begin trackball movement

Synopsis: tcl3dTbStartMotion { toglwin x y }

Description: toglwin : string
 x : int
 y : int

Begin movement of the trackball attached to Togl window "toglwin".
 "x" and "y" give the actual mouse position inside the Togl window.
 This procedure is typically bound to a button press event.
 Example: bind .toglwin <ButtonPress-1>
 "tcl3dTbStartMotion .toglwin %x %y"

See also: tcl3dTbStopMotion
 tcl3dTbMotion

Name: tcl3dTbStopMotion - Stop trackball movement

Synopsis: tcl3dTbStopMotion { toglwin }

Description: toglwin : string

Stop movement of the trackball attached to Togl window "toglwin".
 This procedure is typically bound to a button release event.
 Example: bind .toglwin <ButtonRelease-1>
 "tcl3dTbStopMotion .toglwin"

See also: tcl3dTbStartMotion
 tcl3dTbMotion

Name: tcl3dTbAnimate - Set the trackball animation mode.

Synopsis: tcl3dTbAnimate { toglwin animate }

Description: toglwin : string
 animate : bool

Set the animation mode of the trackball attached to Togl window "toglwin".
If the trackball shall continue spinning after the mouse button has been released, set "animate" to true.
Set "animate" to false, if the trackball should stop spinning after the mouse button has been released.

See also: tcl3dTbStartMotion

Name: tcl3dTbInit - Initialize the trackball module.

Synopsis: tcl3dTbInit { toglwin }

Description: toglwin : string

Initialize the trackball attached to Togl window "toglwin".
This procedure must be called before any other trackball procedures, for example in the Togl create callback.

See also:

Name: tcl3dTbMatrix - Use the trackball matrix rotation

Synopsis: tcl3dTbMatrix { toglwin }

Description: toglwin : string

Use the rotation matrix of the trackball attached to Togl window "toglwin".
The rotation matrix is applied to the top most OpenGL matrix with glMultMatrixf.
This procedure is typically called in the Togl display callback.

See also:

Name: tcl3dTbReshape - Notify trackball about a reshape.

Synopsis: tcl3dTbReshape { toglwin w h }

Description: toglwin : string
 w : int
 h : int

Notify the trackball attached to Togl window "toglwin" that the size of the window has been changed to width "w" and height "h".
This procedure is typically called in the Togl reshape callback.

See also: tcl3dTbInit

Name: tcl3dTbMotion - Move the trackball.

Synopsis: tcl3dTbMotion { toglwin x y }

Description: `toglwin` : string
 `x` : int
 `y` : int

Move the trackball attached to Togl window "toglwin".
"x" and "y" give the actual mouse position inside the
Togl window.

This procedure is typically bound to a mouse motion
event.

Example: `bind .toglwin <B1-Motion>`
 `"tcl3dTbMotion .toglwin %x %y"`

See also: `tcl3dTbStartMotion`
 `tcl3dTbStopMotion`

Implementation file: tcl3dVecMath.tcl

```

Copyright:      2005-2010 Paul Obermeier (obermeier@tcl3d.org)

                See the file "Tcl3D_License.txt" for information on
                usage and redistribution of this file, and for a
                DISCLAIMER OF ALL WARRANTIES.

Module:         Tcl3D -> tcl3dOgl
Filename:       tcl3dVecMath.tcl

Author:         Paul Obermeier

Description:     Tcl module to handle vectors and transformation
                matrices.

Name:           tcl3dVec3Print - Print contents of a 3D vector.

Synopsis:       tcl3dVec3Print { vec { precisionString "%6.3f" } }

Description:     vec : string (Tcl3D Vector Identifier)
                precisionString: string, optional

                Print the contents of 3D Vector "vec" onto
                standard output. "vec" is a Tcl3D Vector of size 3
                and type float or double.

See also:       tcl3dMatPrint

Name:           tcl3dMatPrint - Print contents of a transformation
                matrix.

Synopsis:       tcl3dMatPrint { mat { precisionString "%6.3f" } }

Description:     mat : string (Tcl3D Vector Identifier)
                precisionString: string, optional

                Print the contents of transformation matrix "mat" onto
                standard output. "mat" is a Tcl3D Vector of size 16
                and type float or double.

See also:       tcl3dVec3Print

Name:           tcl3dRadToDeg - Convert angle from radians to degrees.

Synopsis:       tcl3dRadToDeg { ang }

Description:     ang : double

                Return angle "ang" specified in radians in degrees.

See also:       tcl3dDegToRad

Name:           tcl3dDegToRad - Convert angle from degrees to radians.

Synopsis:       tcl3dDegToRad { ang }

Description:     ang : double

                Return angle "ang" specified in degrees in radians.

See also:       tcl3dRadToDeg

```

Implementation file: tcl3dVector.tcl

Copyright: 2005-2010 Paul Obermeier (obermeier@tcl3d.org)

See the file "Tcl3D_License.txt" for information on usage and redistribution of this file, and for a DISCLAIMER OF ALL WARRANTIES.

Module: Tcl3D -> tcl3dOgl
 Filename: tcl3dVector.tcl

Author: Paul Obermeier

Description: Tcl module to handle tcl3dVectors, i.e. contiguous pieces of memory.

Name: tcl3dVector - Create a new Tcl3D Vector

Synopsis: tcl3dVector { type size }

Description: type : string
 size : int

Create a new Tcl3D Vector of size "size" by calling the memory allocation routine new_"type" and create a new Tcl procedure.
 The contents of the new Tcl3D Vector are uninitialized. Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

The following base types are currently supported:

GLbitfield	GLboolean	GLbyte	GLclampd
GLclampf	GLdouble	GLenum	GLfloat
GLint	GLshort	GLsizei	GLubyte
GLuint	GLushort	double	float
int	short	uint	ushort

Note: To get an up-to-date list of wrapped types, issue the command "info commands new_*" after loading Tcl3D or use the script "vectorTypes.tcl" in directory "tcl3dUtil/test".

A detailed description of Tcl3D Vectors can be found in the Tcl3D manual.

See also: tcl3dVectorFromArgs
 tcl3dVectorFromByteArray
 tcl3dVectorFromList
 tcl3dVectorFromPhoto
 tcl3dVectorFromString

Name: tcl3dVectorInd - Get index of a Tcl3D Vector.

Synopsis: tcl3dVectorInd { vec type ind }

Description: vec : string (Tcl3D Vector Identifier)
 type : string
 ind : int

Return the "pointer" to the "ind" element of a Tcl3D Vector. The base Tcl3D Vector is specified with "vec", the type of the Vector is given with "type".

Note: See the description of tcl3dVector for a list of usable types.
 This function may be used in conjunction with OpenGL interleaved vertex arrays. See RedBook demo "aapolyStride.tcl" for an example usage.

See also: `tcl3dVector`

Name: `tcl3dVectorPrint` - Print contents of a Tcl3D Vector.

Synopsis: `tcl3dVectorPrint { vec num { precisionString "%6.3f" } }`

Description: `vec` : string (Tcl3D Vector Identifier)
`num` : num
`precisionString`: string, optional

Print the first "num" elements of Tcl3D Vector "vec" onto standard output.

Note: Tcl3D Vectors behave like C vectors, i.e. they do not have information about its length.

See also: `tcl3dVector`

Name: `tcl3dVectorFromArgs` - Create new Tcl3D Vector from an argument list.

Synopsis: `tcl3dVectorFromArgs { type args }`

Description: `type` : string
`args` : list

Create a new Tcl3D Vector of type "type" from given variable argument list.
Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

Note: See the description of `tcl3dVector` for a list of usable types.

See also: `tcl3dVector`
`tcl3dVectorFromByteArray`
`tcl3dVectorFromList`
`tcl3dVectorFromPhoto`
`tcl3dVectorFromString`

Name: `tcl3dVectorFromList` - Create new Tcl3D Vector from a list.

Synopsis: `tcl3dVectorFromList { type l { maxElems -1 } }`

Description: `type` : string
`l` : list
`maxElems` : int

Create a new Tcl3D Vector of type "type" from given Tcl list "l". If "maxElems" is given and greater than zero, only the first "maxElems" are used.
Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

Note: See the description of `tcl3dVector` for a list of usable types.

See also: `tcl3dVector`
`tcl3dVectorFromArgs`
`tcl3dVectorFromByteArray`
`tcl3dVectorFromPhoto`
`tcl3dVectorFromString`

Name: `tcl3dCharToNum` - Convert character to integer.

Synopsis: `tcl3dCharToNum { char }`

Description: char : character

Convert an ASCII character into the corresponding numeric value.

See also: tcl3dNumToChar

Name: tcl3dNumToChar - Convert integer to character.

Synopsis: tcl3dNumToChar { num }

Description: num : int

Convert a numeric value into the corresponding ASCII character.

See also: tcl3dCharToNum

Name: tcl3dVectorFromString - Create new Tcl3D Vector from a string.

Synopsis: tcl3dVectorFromString { type str }

Description: type : string
str : string

Create a new Tcl3D Vector of type "type" from given string "str".
Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

Note: This version is very slow and is intended only for converting the characters of short text strings into it's numerical values to be used by display lists rendering raster fonts.
See the description of tcl3dVector for a list of usable types.

See also: tcl3dVector
tcl3dVectorFromArgs
tcl3dVectorFromByteArray
tcl3dVectorFromList
tcl3dVectorFromPhoto

Name: tcl3dVectorFromByteArray - Create new Tcl3D Vector from binary string.

Synopsis: tcl3dVectorFromByteArray { type str }

Description: type : string
str : string

Create a new Tcl3D Vector of type "type" from given binary string "str".
Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

Note: See the description of tcl3dVector for a list of usable types.

See also: tcl3dVector
tcl3dVectorFromArgs
tcl3dVectorFromList
tcl3dVectorFromPhoto
tcl3dVectorFromString

Name: tcl3dVectorFromPhoto - Create new Tcl3D Vector from a Tk photo.

Synopsis: `tcl3dVectorFromPhoto { phImg { numChans -1 }
{ scl 1.0 } { off 0.0 } }`

Description: `phImg : string (Photo image identifier)`
`numChans : int`
`scl : double`
`off : double`

Create a new Tcl3D Vector containing the image data of Tk photo "phImg". The created Tcl3D Vector is of type `GL_UNSIGNED_BYTE`. If "numChans" is specified and between 1 and 4, only the first "numChans" are copied into the Tcl3D Vector. Otherwise all channels available in the photo image are used.
"scl" and "off" can be used to scale and offset the pixel values while converting.
Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

See also: `tcl3dVector`
`tcl3dVectorFromArgs`
`tcl3dVectorFromByteArray`
`tcl3dVectorFromList`
`tcl3dVectorFromString`

Name: `tcl3dVectorFromLinspace - Create new linearly spaced Tcl3D Vector.`

Synopsis: `tcl3dVectorFromLinspace { type s e n }`

Description: `type : string`
`s : Start value of type "type"`
`e : End value of type "type"`
`n : int`

Create a new Tcl3D Vector of type "type" and length "n" containing "n" data values linearly spaced between and including "s" and "e".
Type can be any of the following:
`GLubyte, GLushort, GLuint, GLfloat, GLdouble, float, double.`

Return the identifier (i.e. the name of the created Tcl procedure) of the new Tcl3D Vector.

This command implements the functionality of the MATLAB `linspace` command.

See also: `tcl3dVector`
`tcl3dVectorFromArgs`
`tcl3dVectorFromByteArray`
`tcl3dVectorFromList`
`tcl3dVectorFromString`

Name: `tcl3dVectorToList - Copy Tcl3D Vector into a list.`

Synopsis: `tcl3dVectorToList { vec num }`

Description: `vec : string (Tcl3D Vector Identifier)`
`num : int`

Copy "num" elements of Tcl3D Vector "vec" into a Tcl list and return that list.

Note: This version is slow and is intended only for converting 3D vectors or transformation matrices into Tcl lists.

See also: `tcl3dVectorFromList`

tcl3dVectorToByteArray
tcl3dVectorToString

Name: tcl3dVectorToString - Copy Tcl3D Vector into a string.

Synopsis: tcl3dVectorToString { vec }

Description: vec : string (Tcl3D Vector Identifier)

Interpret the elements of Tcl3D Vector "vec" (which must be of type GLubyte) as a null-terminated string and return that string.

Note: This version is slow and is intended only for short text strings. Use this function for example to convert the information returned by a GLSL shader.

See also: tcl3dVectorFromString
tcl3dVectorToByteArray
tcl3dVectorToList

Name: tcl3dVectorToByteArray - Copy Tcl3D Vector into a binary string.

Synopsis: tcl3dVectorToByteArray { vec numBytes {srcOff 0} {destOff 0} } {

Description: vec : string (Tcl3D Vector Identifier)
numBytes : int
srcOff : int
destOff : int

Copy "numBytes" elements of Tcl3D Vector "vec" into a Tcl binary string and return that string. The Tcl3D Vector has be of type GLubyte. "srcOff" and "destOff" may be used optionally to specify an offset into the source and the destination.

See also: tcl3dVectorFromByteArray
tcl3dVectorToList
tcl3dVectorToString